



Standard Trough Lighting

(7 different angle positions)

The trough lighting from Lightsign is an epoxy powder coated extruded aluminium with press formed end caps and a Perspex front. Our tough system comes in 6 metre sections and can be cut to any size or extended using an internal coupler. The trough comes complete with wall mounting brackets and an extension cut to a size of 150mm. The angle of the trough can be adjusted using one of seven different positions. It is super bright and energy efficient!

LED TROUGH LIGHTING

The trough lighting from Lightsign is a specifically designed product that is used for external fascia lighting.

The system is an epoxy powdercoated aluminium profile with acrylic endcaps that houses IP67 rated 1000lumen per meter LED light engine which is diffused by a prismatic clear acrylic that evenly distributes the light without affecting the output intensity.

The standard length is up to 6 meters but our troughand can be cut to any size or extended using an internal coupler.

The trough comes complete with wall mounting brackets and an extension cut to a standard size of 150mm. The angle of the trough can be adjusted using one of seven different positions. It has a diameter of 78mm. It is superbright and energy efficient.



Power Supply	230V AC
Power Consumption	14.4 W/m
Colour Temperature	3000K or 5000K
Lumens	1000Lm/m
IP Rating	IP67
Material	Aluminium
Paint Colour	Black, White & Mill Finish
Warranty	2 years
Working Temperature	-40°C to 70°C
Cer tification	CE & RoHS

EXAMPLES

